

GAS BBQ INSTRUCTIONS



Setup & Use

- Ensure that the hoses and fitting are properly connected. Gas threads tighten anti-clockwise. Test fittings for gas leak with soapy water.

Lighting

- Turn the knobs to off position and turn the gas on at the bottle
- To light the outside burner rail – turn the knob to the high position by holding knob down and turning
- Keep the knob depressed and light burner
- If the burner doesn't light on the first attempt, shut off gas at bottle, wait a minute and repeat the above steps.
- To light inner burner, repeat above process
- Adjust the flame height to the desired cooking level

Precautions:

- This unit can get very hot, take care to avoid contact with hot surface
- There is no gas cut-out facility on this barbeque, gas must be turned off at the bottle when you shut down the barbeque

Troubleshooting:

- **No gas:** Check that gas bottle is turned on and hose is securely connected
- **Safety:** Ensure there is adequate ventilation behind and above bbq
 - Minimum distance behind – 30cm
 - Minimum distance above – 200cm
- **If you smell gas:**
 - Turn off the gas supply at bottle and extinguish all naked flames
 - Ventilate the area and check unit for leaks

Please note: AABCO takes all precautions to ensure that this unit is properly maintained and checked prior to delivery. However, damage may occur during transport, installation or usage.

BBQ should not be used in windy areas as this may blow out the flame and will lower the cooking temperature.

Should you notice or suspect any damage or faulty operation, please do not use this unit.